

Technical Data Sheet

CitcoWater.com



CHEMICAL
SOLUTIONS



AULCLEAR²

cationic coagulant

AulClear 2

Cationic Coagulant

AulClear 2 is a coagulant used for the clarification of wastewater. It is used in a broad range of liquid clarification processes both in municipal and industrial water and wastewater treatment applications for the settling of sludge, clarifying of wastewater, and precipitating out of phosphorus. AulClear 2 is effective over a pH range of 6.5 -10.

Other polymers used for clarification will decrease the dissolved oxygen level. This is a large problem for wastewater treatment plants. AulClear 2 works differently in that it does not decrease the wastewater pH, but increases the dissolved oxygen level.

Directions: For your protection, always wear the proper safety attire when using AulClear 2. For instructions specific to your application, contact your CITCO Water technical consultant.

Do not allow AulClear 2 to freeze Always follow recommendations on the Safety Data Sheet. .



Specifications

- Specific gravity: 1.38 PPG
- pH: 2.47
- Appearance: colorless/light amber
- Odor: odorless



Applications

- DAF systems
- Belt filter press
- Municipal wastewater
- Industrial wastewater
- Water treatment



Availability

AulClear 2 is available in 5-gallon pails, 55-gallon drums, and 330-gallon totes.



info@CitcoWater.com
customerservice@CitcoWater.com
800.999.3484

CITCO WATER

AulClear 2